

BERKSHIRE HDPA-

shown on front: 25535 6x24 Hickory

Berkshire^{HDP} evokes the history and romance of the rugged yet refined American Northeast. Rich colors and an intricate surface texture give it the look and feel of reclaimed lumber that has already withstood a lifetime. The character of historied timbers shows through with every plank. Using our proprietary HDP – High Definition Porcelain® printing, we create an amazing wood look that is almost indistinguishable from the real thing.

A color palette named for five wood varieties: Oak, Hickory, Olive, Walnut, and Maple encompass the majestic beauty of old growth forests. The tight grains, tone variations, and natural inconsistencies of real wood are precisely replicated. Available in 6x24 and 8x36 pressed planks, 12x12 parquet mosaics, and a 3x24 bullnose, this color body porcelain floor and wall tile lends rustic charm to any space.

below: **25525 6x24** Oak







25525 6x24 Oak



25525 8x36 Oak



25525/M12RECOak Parquet Mosaic

HICKORY



25535 6x24 Hickory



25535 8x36 Hickory



25535/M12RECHickory Parquet Mosaic

OLIVE



25555 6x24 Olive



25555 8x36 Olive



25555/M12RECOlive Parquet Mosaic

WALNUT



25585 6x24 Walnut



25585 8x36 Walnut



25585/M12RECWalnut Parquet Mosaic

MAPLE



25595 6x24 Maple



25595 8x36 Maple



25595/M12RECMaple Parquet Mosaic



above: 25585 6x24 Walnut

Porcelain Technical Data Properties (Floor)	ASTM®	ANSI®	Results ¹
DCOF AcuTest®2	A137.1	≥ 0.42	Pass
Surface Hardness	Mohs Scale	N/A	7 Mohs
Break Strength	C-648	≥ 250 lbf.	≥ 474 lbf. avg.
Water Absorption	C-373	≤ 0.5%	≤ 0.5%³
Intended Use ⁴	N/A	N/A	Residential Light Commercial

¹ Values are offered in good faith as being accurate and typical of normal production. Due to the natural variation of raw materials and manufacturing processes, the values of the purchased product for any particular installation may vary.

Typical Uses

Berkshire HDP color body porcelain floor and wall tile is appropriate for residential and commercial wall, countertop, backsplash, and most floor applications.

Notice: Not all flooring products are suitable for wet areas, specialized applications, or commercial use. Please refer to the American National Standard Specifications for Ceramic Tile (ANSI® A137.1) for ceramic, stone, and glass installation for specific usage and installation information.

This product will contribute to USGBC LEED® points and the ANSI® approved NAHB® Green Building Points.

Color, texture, and finish variations may occur due to the nature of the product.

Color reproductions in this printed piece may vary from actual tile colors. Final selection should be made from actual tile samples.

Field Tile Nominal Size (in) ¹	Metric (cm)	Pcs./Sq Ft ²	Thickness ³	Edge
6x24	15x60	1	9mm⁴	Pressed
8x36	20x90	.5	9mm⁴	Pressed

¹These values may vary from lot to lot.

 $^{^{\}rm 4}$ In order to enhance manufacturing efficiencies this product has been modified to a 9mm thickness. During implementation of this modification, some 11mm products will remain available. Please confirm the thickness of your product at time of order.

Trim	Shape	Sku	Nominal Size (in) ¹	Metric (cm)
Bullnose		P43N9	3x24	7.5x60

¹These values may vary from lot to lot.

Color Variation V2 Slight Variation Clearly distinguishable differences in texture and/or pattern with similar colors.

















 $^{^2}$ ANSI® A137.1 standard, ceramic tiles selected for level interior spaces expected to be walked upon when wet must have a minimum wet DCOF AcuTest® value of 0.42.

³ Average production value.

²These values are based on actual sizes including the grout joint.

³ May not apply to textured surfaces or tiles with uneven back patterns such as mesh mounted mosaics.